

HYDRA RAM[®]

ADVANCED DEMOLITION EQUIPMENT



HYDRAULIC PILE DRIVERS/COMPACTORS
FULL RANGE FROM 110 TO 1150 KG
8 MODELS FOR CARRIERS FROM 0.8 TO 38 TONS

HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT

SPECIFICATIONS

MODEL		HC-100	HC-180/2	HC-250/2	HC-420/2
WEIGHT	(kg)	110	160	230	400
OILFLOW	(l/pm)	20-30	25-40	25-40	55-85
PRESSURE	(bar)	120-140	120-140	120-140	120-140
FREQUENCY	(rpm)	2200-2600	2200-3000	2200-3000	2100-2600
OUTPUT POWER	(KN)	10	18	25	50
EXCAVATOR	(t)	0.8 – 2.0	2.0 – 3.5	3.5 – 7.0	6.0 – 10.0
MODEL		HC-600/2	HC-900/2	HC-1200/2	HC-1500/2
WEIGHT	(kg)	580	850	950	1150
OILFLOW	(l/pm)	55-85	100-130	170-210	180-220
PRESSURE	(bar)	120-140	120-140	190-215	200-220
FREQUENCY	(rpm)	2100-2600	2200-2500	2400-2900	2400-2900
OUTPUT POWER	(KN)	55	95	155	205
EXCAVATOR	(t)	8.0 – 16.0	15 – 28	20 – 35	22-38

(DEALER)

HYDRA RAM®
ADVANCED DEMOLITION EQUIPMENT

HYDRARAM b.v.
Meander 7
NL 9231DB SURHUISTERVEEN
The Netherlands

tel. +31 512-365981
fax. +31 512-365761
www.hydraram.com
info@hydraram.com

*SPECIFICATIONS IN THIS BROCHURE ARE SUBJECT TO CHANGE WITHOUT NOTICE