



WOOD CHIPPER
STUMP GRINDERS
HFG I
HFG II
HFG IV
HFG V
HFG VI
HFZ FEINZERKLEINERER
WOOD AND GARBAGE
CRUSHERS
BIO SHREDDER

CONTACTS

PHONE

0049 05933 / 9318 - 0

EMAIL

INFO@HUSMANN-
WEB.DE

General information

Technical Specifications

Accessories

Videos

Technical Specifications: HFG V

Type series:

Type	Drive	Output
HFG V (80 km/h axle)	Turbo-Diesel, Euro III	354 kW
HFG V E/S stationary system with steel supports and switching cabinets at the system	E-Motor	250 kW

Technical Equipment:

Undercarriage:	<ul style="list-style-type: none"> Welded steel profile construction with towing device pursuant to DIN
Undercarriage:	<ul style="list-style-type: none"> Tandem low-loader unit approx. 18 to. TÜV acceptance for 80 km/h axle
Supply belt:	<ul style="list-style-type: none"> Highly wear-proof forged special chain Infeed belt width: 1,500 mm Infeed belt length: 4,000 mm
Brake system:	<ul style="list-style-type: none"> Double-line compressed-air brake system with ABS
Tyres:	<ul style="list-style-type: none"> 4 size 385 / 65 R 22.5
Lighting:	<ul style="list-style-type: none"> Pursuant to StVO
Hydraulic system:	<ul style="list-style-type: none"> Infeed roll with supply belt with one separate drive and gear each. The infeed belt and infeed roll speeds can be set smoothly. Overload protection by speed monitoring and reversing device. Hydraulic tank with a content of 220 litres.
Infeed:	<ul style="list-style-type: none"> The infeed roll is hydraulically driven, mounted in a swinging arrangement and is guided by 2 racks. The infeed opening is approx. 540 mm high and 1,500 mm wide.
Striking mechanism:	<ul style="list-style-type: none"> 42 hammers Hammer tips can be replaced separately. Striking mechanism width: 1,500 mm Rotor diameter: 1,000 mm Rotor speed: 1,000 rpm
Engine:	<ul style="list-style-type: none"> CAT turbo diesel with an output of P = 354 kW, EURO III
Drive:	<ul style="list-style-type: none"> Composite V-belts (8-groove) with hydr. belt tensioners as coupling
Dimensions:	<ul style="list-style-type: none"> See set-up plan and scope of delivery Total length: approx. 8,900 mm Width: 2,470 mm Height: approx. 3,800 mm Towing eyelet height 900 mm Hopper opening length 4,800 mm Hopper opening width 1,900 mm
Tank volume:	<ul style="list-style-type: none"> 516 litres
Throughput:	<ul style="list-style-type: none"> 100-150 m³/h and more, depending on material
Paint:	<ul style="list-style-type: none"> Special paint – all RAL colours (standard RAL 5010)