



8014 CTS

8016 CTS

8018 CTS

8020 CTS



Peso operativo de balancín estándar	(kg)	1564	1590	1662	2060
Potencia bruta del motor	(hp/kW)	19 / 14.2	19 / 14.2	19 / 14.2	19 / 14.2
Longitud de balancín	(mm)	1161	1161 (1261)	1161 (1261) (1500)	1261
Profundidad de excavación	(mm)	2044	2044 (2144)	2142 (2242) (2477)	2430
Alcance a nivel del suelo	(mm)	3764	3764 (3847)	3865 (3949) (4184)	4065
Altura de descarga	(mm)	2501	2501 (2559)	2568 (2626) (2765)	2772
Capacidad del depósito de combustible	(Ltr)	23.5	23.5	23.5	23.5
Fuerza de arranque del cazo	(kN)	13.5	16.2	16.2	19
Fuerza de arranque del balancín	(kN)	8.0	8.0	9.2	9.3
Caudal de la bomba	(Ltr/min)	39.2	39.2	43.6	43.6
Anchura de la máquina	(mm)	980	980	980 – 1340	1002 – 1362

8025 ZTS	8030 ZTS	8035 ZTS	8040 ZTS	8045 ZTS	8050 ZTS / RTS
					
2685	3217	3651	4300	4750	5162
28 / 20.9	28 / 20.9	32 / 24	46.4 / 34.1	46.4 / 34.1	46.4 / 34.1
1100	1300	1530	1525	1725	1725 or 1900
2580	2794	3173	3341	3542	3542 or 3717
4691	4901	5315	5613	5844	5844 or 6001
3158	3205	3482	3843	3977	3977 or 4102
40	40	40	68	68	68
24	28	32	37.1	42.2	42.2
15	17	20	23	26.1	26.1 or 23.75
102	102	108	169	169	169
1550	1650	1750	1980	1980	1980