



# EISEMANN

## P 4401 DE

Order Number 083444

2 protective contact sockets (16 A) waterproof cutout.  
Automatic shut-down if low oil level is detected.



Attribute	Unit	Value
Genset type		Synchronous
Electrical capacity (1~) cos $\phi$ 1,0	VA	3300
Voltage (1~)	V	230
Maximum sum. current (1~)	A	14.4
Current (Schuko 1~)	A	14.4
Starting current	A 1~	14.4
Frequency	Hz	50
Protection		IP 23
Engine type		HATZ 1B30
Cylinders		1
Speed	U min <sup>-1</sup>	3000
Fuel type		Diesel
Engine oil capacity	l	1.1
Engine power	kW	4.6
Cooling	engine / generator	air / air
Fuel capacity	l	5
Operation time 3/4 load	h	6.6
Weight	kg	75
Dimensions	mm	740 x 500 x 530
Acoustic power	dB(A)	100
Acoustic pressure	dB(A)	72

Related equipment	Order Number	Related equipment	Order Number
Exhaust hose, 904872	904872	Adapter for exhaust hose, 904880	904880
Earthing set, 908250	908250	Isolation control device, external, with cut-of ...	018520
Chassis, 988548	988548	Lifting set, 911643	911643
Carrying handles, 900566	900566	Professional light pole, 908510	908510
Additional fuel tank, 50l, 923995	923995	Additional fuel tank, 100l, 923998	923998
Additional fuel tank, 150l, 923963	923963	Assembly-kit for additional fuel tank, 923994	923994
Starterbatterie 020316	020316		

GEKO

EISEMANN

Metallwarenfabrik Gemmingen GmbH  
Industriestrasse 1 D-75050 Gemmingen

Telefon +49 (0) 7267 806-0  
www.metallwarenfabrik.com

Fax +49 (0) 7267 806-100  
info@metallwarenfabrik.com