

Specification	light duty		heavy duty			heavy duty fixed			heavy duty reinforced		
	EU	US	RM 705D	RM 708D	RM 712D	RM 714D	RM 716D	RM 723D	RM 727D	RM 729D	RM 733D
Poids prêt à utiliser (y compris suspension)	kg		240	390	825	1205	1265	1800	2025	2220	2425
Débit d'huile (max.) / ouvrir-fermer	l/min		25	30	45	80	80	120	120	120	120
Pression de service (max.) / ouvrir-fermer	bar		300	320	320	320	320	320	320	320	320
Débit d'huile (max.) / tourner	l/min		20	25	30	30	30	30	30	30	30
Pression de service (max.) / tourner	bar		300	300	300	170	170	170	170	170	170
Longueur totale (ouvert)	mm		1000	1480	1930	1800	1800	2060	2280	2280	2280
Largeur totale	mm		370	450	600	850	1000	1000	1000	1150	1300
Temps de cycle	s		4	4	5	5	5	5	5	5	5
Capacité	dm³		40	100	220	500	600	800	1000	1150	1300
Poids de la machine conseillée	t		3 - 6	6 - 10	10 - 16	13 - 19	14 - 21	19 - 26	22 - 29	24 - 31	26 - 34

