



Actros 1845 LS 4x2

Application type	Long-distance transport
Vehicle type	Tractor
Weight	18 t / 40 t (permitted solo gross weight/gross combination weight)
Drive type	4x2
Engine output	330 kW (449 hp), R 6, 2200 Nm at 1100 rpm
Emission standard	Euro VI
Cab	L cab ClassicSpace (width 2.30 m) Cabs with engine tunnel (height 170 mm), for storage compartment on left
Wheelbase	3700 mm
Suspension	Air suspension on all axles
Frame	Standard frame
Tyres axle 1	
Tyres axle 2	



Equipment

Safety & Assistance systems

Predictive Powertrain Control

LED daytime running lamps

ADR chassis

Electronic braking system with ABS and ASR

Parking brake, acoustic warning

Disc brakes on front and rear axle

Brake and electrical connections, low

Compressed air supply connection, front

Flashing brake lights during emergency braking

Powertrain

Speed limiter, 90 km/h (56 mph), ECE

Bottom shell to prevent swirling-up of dust

Air compressor, 2-stage, for optimised consumption

Exhaust brake, standard system

Water pump, governed

Radiator shutter

Torque increase in 12th gear

Air intake behind cab, mounted

Mercedes PowerShift 3
Single-disc clutch
Transmission G 211-12/14.93-1.0
Front axle 8.0 t
Front axle with air suspension
Differential lock, rear axle
Front axle, offset version
Rear axle, crown wheel 440, hypoid, 13.0 t
Axle ratio $i = 2.412$
15-degree tapered rims, 9.00 x 22.5

Cab

Windscreen, tinted
Kerb mirror
MirrorCam
Power windows, all-round
Driver's suspension seat, standard
Fold-up co-driver's seat
Driver's seat backrest, release mechanism
Seat cover, flat-weave fabric
Luxury bed, bottom
Display, trailer data, in instrument panel
Tachograph, 1 day + 2 drivers, modular
Cruise control
On-Board Diagnosis
Travel computer
Maintenance system
Entrance lamps, in door panel
Multimedia Cockpit
FleetBoard Eco Support
Comfort telephony, wireless charging
Standard loudspeaker
Socket, 24 V/15 A, co-driver footwell
Pollen filter
Document stowage space, A4 size
Bottle holder
Stowage compartment exterior flap, right
Stowage compartment exterior flap, left
Cab entrance, left/right, rigid
Step, behind cab, left
Cab, reinforced
Roof hatch/vent, roof
Cab rear wall, without window
2 remote control keys
Locking system, with central locking
Step plate above frame, partial cover

Chassis

Exhaust system, tailpipe to right and outwards
Cable remote control for air suspension
Frame overhang 750 mm
Cab tilting mechanism, mechanical-hydraulic
Air reservoir, steel
Cab mountings, standard, steel-sprung
Battery carrier, batteries side by side
End cross member, neutral position
Front underride guard (ECE), aluminium
Wing, for chassis transit
Batteries 2 x 12 V/170 Ah, low-maintenance
Bumper, with plastic corners
Bumper centre section with towing eyes
Aerodynamic underbody panelling
Tank cross-section, narrow
Tank cross-section, high
Tank, 390 l, left, 650 x 700 x 1000 mm, aluminium
AdBlue tank, 60 l, left
Main tank, left
Trailer socket, 24 V, 15-pin
Fifth-wheel coupling with hole pattern

Air deflectors, corner panels

A-pillar trim

Power steering pump, uncontrolled

Steering, single-circuit

There may have been changes to the product since publication. The manufacturer reserves the right to make changes in design or form and changes in colours, in so far as the changes or deviations can be deemed reasonable (for the purchaser) taking into account the interests of the seller. The illustrations may also include accessories and optional extras that are not included in the standard scope of delivery.

