



Actros 1851 LS 4x2

Application type	Long-distance transport
Vehicle type	Tractor
Weight	18 t / 40 t (permitted solo gross weight/gross combination weight)
Drive type	4x2
Engine output	375 kW (510 hp), R 6, 2500 Nm at 1100 rpm
Emission standard	Euro VI
Cab	L cab ClassicSpace (width 2.30 m) Cabs with engine tunnel (height 170 mm), for storage compartment on left
Wheelbase	3700 mm
Suspension	Air suspension on all axles
Frame	Standard frame
Tyres axle 1	
Tyres axle 2	



Equipment

Safety & Assistance systems
Predictive Powertrain Control
LED daytime running lamps
ADR chassis
Electronic braking system with ABS and ASR
Parking brake, acoustic warning
Disc brakes on front and rear axle
Brake and electrical connections, low
Compressed air supply connection, front
Flashing brake lights during emergency braking
Powertrain
Speed limiter, 90 km/h (56 mph), ECE
Bottom shell to prevent swirling-up of dust
Exhaust brake, standard system
Air compressor, 2-stage, for optimised consumption
Water pump, governed
Radiator shutter
Air intake behind cab, mounted
Single-disc clutch

Mercedes PowerShift 3
Transmission G 281-12/14.93-1.0
Front axle 8.0 t
Front axle, offset version
Differential lock, rear axle
Front axle with air suspension
Rear axle, crown wheel 440, hypoid, 13.0 t
Axle ratio i = 2.412
15-degree tapered rims, 9.00 x 22.5

Cab

Windscreen, tinted
MirrorCam
Kerb mirror
Power windows, all-round
Driver's suspension seat, standard
Fold-up co-driver's seat
Seat cover, flat-weave fabric
Driver's seat backrest, release mechanism
Luxury bed, bottom
Display, trailer data, in instrument panel
Tachograph, 1 day + 2 drivers, modular
Cruise control
Travel computer
On-Board Diagnosis
Maintenance system
Entrance lamps, in door panel
Multimedia Cockpit
FleetBoard Eco Support
Comfort telephony, wireless charging
Standard loudspeaker
Socket, 24 V/15 A, co-driver footwell
Pollen filter
Bottle holder
Document stowage space, A4 size
Stowage compartment exterior flap, left
Stowage compartment exterior flap, right
Cab entrance, left/right, rigid
Step, behind cab, left
Cab, reinforced
Roof hatch/vent, roof
Cab rear wall, without window
2 remote control keys
Locking system, with central locking
Step plate above frame, partial cover

Chassis

Exhaust system, tailpipe to right and outwards
Cable remote control for air suspension
Frame overhang 750 mm
Cab tilting mechanism, mechanical-hydraulic
Air reservoir, steel
Battery carrier, batteries side by side
Cab mountings, standard, steel-sprung
End cross member, neutral position
Front underride guard (ECE), aluminium
Wing, for chassis transit
Batteries 2 x 12 V/170 Ah, low-maintenance
Bumper, with plastic corners
Bumper centre section with towing eyes
Aerodynamic underbody panelling
Tank cross-section, narrow
Tank cross-section, high
Tank, 390 l, left, 650 x 700 x 1000 mm, aluminium
AdBlue tank, 60 l, left
Main tank, left
Trailer socket, 24 V, 15-pin
Fifth-wheel coupling with hole pattern
Air deflectors, corner panels

A-pillar trim

Power steering pump, uncontrolled

Steering, single-circuit

There may have been changes to the product since publication. The manufacturer reserves the right to make changes in design or form and changes in colours, in so far as the changes or deviations can be deemed reasonable (for the purchaser) taking into account the interests of the seller. The illustrations may also include accessories and optional extras that are not included in the standard scope of delivery.

