



Arocs 3363 LS 6x4

Application type	Construction transport
Vehicle type	Tractor
Weight	26 t / 40 t (permitted solo gross weight/gross combination weight)
Drive type	6x4
Engine output	460 kW (625 hp), R 6, 3000 Nm at 1100 rpm
Emission standard	Euro VI
Cab	L cab ClassicSpace (width 2.30 m) Cabs with flat floor
Wheelbase	3300 mm
Suspension	Rear air suspension
Frame	Standard frame
Tyres axle 1	
Tyres axle 2	Bridgestone 315/80 R 22,5 Regio (Traction/M+S)
Tyres axle 3	Bridgestone 315/80 R 22,5 Regio (Traction/M+S)



Equipment

Safety & Assistance systems
Predictive Powertrain Control
Electronic braking system with ABS and ASR
Parking brake, acoustic warning
Disc brakes on front and rear axle
Brake and electrical connections, high
Compressed air supply connection, front
Flashing brake lights during emergency braking
Powertrain
Speed limiter, 90 km/h (56 mph), ECE
Bottom shell to prevent swirling-up of dust
Turbocompound
Air compressor, 2-cylinder
Exhaust brake, standard system
Insect screen in front of cooling system
Engine mounts, reinforced
Air intake behind cab, mounted
Mercedes PowerShift 3
Transmission G 330-12/11.63-0.77

Double-disc clutch
 Transmission oil cooling
 Transmission support arms, optimised for removal
 Front axle 7.5 t
 Differential lock, rear axle
 Front axle, straight version
 Rear axle, crown wheel 440, hypoid, 13.0 t
 Axle ratio $i = 4.300$
 15-degree tapered rims, 9.00 x 22.5

Cab

Windscreen, tinted
 Kerb mirror
 Mirror cover, construction vehicle
 Sunblind, side, driver's side
 Power windows, all-round
 Driver's suspension seat, standard
 Fold-up co-driver's seat
 Seat cover, flat-weave fabric
 Driver's seat backrest, release mechanism
 Luxury bed, bottom
 Display, trailer data, in instrument panel
 Compressed-air connection, in cab
 Tachograph, 1 day + 2 drivers, modular
 Cruise control
 Travel computer
 On-Board Diagnosis
 Maintenance system
 Compressed-air gun, with hose
 Entrance lamps, in door panel
 Multimedia Cockpit
 FleetBoard Eco Support
 Standard loudspeaker
 Socket, 24 V/15 A, co-driver footwell
 Pollen filter
 Bottle holder
 Document stowage space, A4 size
 Stowage compartment lid, driver and co-driver side
 Stowage compartment exterior flap, left
 Stowage compartment exterior flap, right
 Door extension
 Cab entrance, left/right, rigid
 Step, behind cab, left
 Cab, reinforced
 Roof hatch/vent, roof
 Cab rear wall, without window
 2 remote control keys
 Locking system, with central locking
 Step plate above frame, partial cover

Chassis

Exhaust system, tailpipe to right and outwards
 Cable remote control for air suspension
 Front spring, 7.5 t, 2-leaf
 Stabiliser, front axle
 Frame overhang 750 mm
 Cab tilting mechanism, mechanical-hydraulic
 Air reservoir, steel
 Cab mountings, comfort, steel-sprung
 Battery carrier, batteries side by side
 End cross member, neutral position
 Front underride guard (ECE), aluminium
 Wing, for chassis transit
 Batteries 2 x 12 V/170 Ah, low-maintenance
 Alternator 28 V/100 A
 Bumper centre section w. towing eyes, coupling jaw
 Bumper, with steel corners
 Tank cross-section, narrow
 Tank cross-section, high

Tank, 290 l, left, 650 x 700 x 750 mm, aluminium

AdBlue tank, 60 l, left

Main tank, left

Trailer socket, 24 V, 15-pin

Fifth wheel angle, extended, h = 50 mm

A-pillar trim

Air deflectors, corner panels

Steering, single-circuit

Power steering pump, uncontrolled

There may have been changes to the product since publication. The manufacturer reserves the right to make changes in design or form and changes in colours, in so far as the changes or deviations can be deemed reasonable (for the purchaser) taking into account the interests of the seller. The illustrations may also include accessories and optional extras that are not included in the standard scope of delivery.

