

Platform

0.76 m x 1.22 m low mount platform

Side entry with inward swing gate

Multiple function operation

Full proportional drive joystick control with integral thumb steer switch

Full proportional main boom and swing joystick control

Variable speed dial control for lower boom, telescope, jib and platform rotate

Selectable creep speed on drive / lift and swing functions

1.24 m articulating jib

JibPLUS® with 4 way axis 1.22m Jib

180 degree powered platform rotator

Platform console machine status light panel ¹

Load sensing system

AC power cable to platform

Functional Equipment & Accessories

3 degree tilt alarm and indicator light

Non mark solid rubber tyres

Pothole protection system

1.22m narrow frame

Lifting/tie down lugs

Ground control selector switch with key lock

Battery condition indicator

Hour meter

Horn

Manual descent system

Available Options

0.76 m x 1.52 m low mount platform

All motion alarm

Alarm package ²

Platform worklights

Head and tail lights

Amber strobe light

Plugs & Sockets

Acrylic console shield

Cylinder bellows

Platform tool tray

Corner storage tray

Power & Transmission

Two Wheel Direct Electric Drive

8 x 6V 370 A/hr deep cycle batteries

Automatic traction control

Programmable "Personality" settings

On-board self-diagnostic testing

Enclosed battery / electrical compartment

23 amp automatic battery charger

Automatic rear wheel brakes

Sculptured ABS hoods

¹ Provides indicator lights at platform control console for system distress, low battery, tilt light, and foot switch status.

² Includes all-motion alarm and amber strobe light.

JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

Printed in UK
 FORM No.: DS057-0208-500
 PART NO.: DS057-ENGLISH



E300AJP

Platform height	9.14 m
Horizontal outreach	6.10 m
Up and over height	3.99 m
Swing (non-continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	1.24 m
Jib - range of articulation	144° Vertical (+84°/ -60°)
JibPLUS™ - range of articulation	180° Horizontal
A. Platform size	0.76 m x 1.22 m
B. Overall width	1.22 m
C. Tailswing (working condition)	Zero
D. Stowed height	2.01 m
E. Stowed length	5.70 m
F. Wheelbase	1.66 m
G. Ground clearance	0.10 m
Machine weight ¹	7,200 kg
Maximum ground bearing pressure	9.1 kg/cm ²
Drive speed	4.8 km/h
Gradeability	25%
Tyres	25 x 7-12 Non marking
Turning radius – inside	1.52 m
Turning radius – outside	3.10 m
Electrical system	48V DC
Batteries	8 x 6V 370 A/hr
Drive motors	Dual Electric Traction
Brakes	Automatic Spring Applied
Hydraulic motor	Perm. Magnet
Hydraulic pump	Gear Pump
Hydraulic system	15 L

