

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler

Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504

Version STANDARD
 Type TT
 Tire Size 7.50 - 16
 PR 6



Dimensions (U/M International standard)

Section Width (mm) 209
 Overall Diameter (mm) 803
 Static Loaded Radius (mm) 372
 Rolling Circumference (mm) 2393
 SRI 390
 Rim Rec 5.50 F
 Rim Alt 4.50 E ; 5.00 F ; 4.00 E ; 5 K ; 6 LB ; 6.00 F

LOAD CAPACITY TABLE (kg)

km/h / bar	2.30
10 FR	1260
25 FR	1070
30 FR	1010
40 FR	900
10 DW	880
25 DW	750
30 DW	705
40 DW	630

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%