



For more information, email: [kuk\\_g.marketing@kubota.com](mailto:kuk_g.marketing@kubota.com) or call: 01844 268200

[www.kubota.co.uk](http://www.kubota.co.uk)   

# B2

## KUBOTA DIESEL TRACTOR B2 Series (B2231/B2261/B2311)

Three new models with the power and versatility you need to get the job done quickly and efficiently

For Earth, For Life  
Kubota



ENHANCED

COMFORT DESIGN SAFETY AND PERFORMANCE

**EASY OPERATION**

Ergonomic control layout as well as a redesigned display unit to make working more comfortable

**ROPS OR CAB**

Available as either a cabbed or ROPS model.

**BI-SPEED TURN**

Kubota's bi-speed system allows you to have a significantly smaller turning circle, allowing for less tyre wear, better ground-conservation and a more efficient day.

**MID AND REAR PTO**

The B2 Series compact tractors come with a mid and rear PTO (Power Take Off) to allow you to fit a range of implements.

**TURF AND AGRICULTURAL TYRES**

Available with both turf and agricultural tyres - allowing you to work effectively in all environments.



SPECIFICATIONS ALL THE ESSENTIAL TECHNICAL INFORMATION

MODEL	B2231	B2261	B2311
<b>PTO POWER</b>	12.5kW (17.0PS)	14.6kW (19.9PS)	17.4kW (23.7PS)
<b>ENGINE</b>	KUBOTA		
Manufacturer	KUBOTA		
Model	D1105	D1305	V1505
Type	Indirect injection, vertical, water-cooled, 4 cycle diesel		
Number of cylinders	3	3	4
Bore and stroke	78 x 78.4mm	78 x 88mm	78 x 78.4mm
Total displacement	1123cm <sup>3</sup>	1261cm <sup>3</sup>	1498cm <sup>3</sup>
Engine Gross Power <sup>1</sup>	16.9kW (23.0PS)	19.1kW (26.0PS)	22.8kW (31.0PS)
Rated Revolution	2500rpm		
Maximum Torque	71.3Nm (7.27kgfm)	84.0Nm (8.57kgfm)	97.9Nm (9.09kgfm)
Battery	12 V, RC: 80min, CCA (SAE) : 430 A, CCA (EN) : 360 A		
<b>CAPACITIES</b>			
Fuel Tank	27L	27L	27L
Engine Crankcase (with filter)	3.1L	4.0L	4.0L
Engine Coolant	4.6L	4.6L	4.6L
Transmission Case	17.0L	17.0L	17.0L
<b>DIMENSIONS</b>			
Overall Length (ROPS / CAB)	2624mm / 2781mm	2624mm / 2781mm	2830mm / 2900mm
Overall Width	1234mm	1249mm	1365mm
Overall Height (ROPS / CAB)	2327mm / 2087mm	2353mm / 2112mm	2327mm / 2140mm
Wheel Base (ROPS / CAB)	1500mm / 1560mm	1500mm / 1560mm	1666mm / 1666mm
Minimum Ground Clearance	265mm	290mm	318mm
Tread (front / rear)	832mm / 986mm	830mm / 1006mm	936mm / 1050mm
<b>WEIGHT</b>			
ROPS / CAB	780kg / 1010kg	790kg / 1020kg	850kg / 1070kg
<b>CLUTCH</b>	N/A		
<b>TRAVELLING SYSTEM</b>			
Steering	Hydraulic power steering		
Transmission	Main-hydrostatic transmission, 3 range gear shift		
Brake	Wet disk type		
Minimum Turning Radius (with brake)	2.1m		
<b>HYDRAULIC UNIT</b>			
Hydraulic Control System	Position control		
Pump Capacity	3P: 18.9L/min, power steering : 14.2L/min		
3-Point Hitch	SAE Category 1		
Max. Lift Force at lift points	970kg		
600mm behind	760kg		
<b>PTO</b>			
Rear-PTO / Mid-PTO	SAE 1-3/8, 6 splines / USA No.5 (KUBOTA 10-tooth) involute spline		
PTO/Engine Speed	540 / 2400 / 2500 / 2500		
<b>LEVEL OF PROTECTION (HAZARDOUS SUBSTANCES)<sup>2</sup></b>	ROPS : N/A / CAB: Category 1		

The company reserves the right to change the above specifications without notice. 1 - manufacturer's estimate 2 - according to EN 15695-1:2009