

**HOLDER  
B/C SERIES**



B 55 SC



C 55 SC



C 65 SC / TC



C 70 SC / TC

	1-person-cab		1- / 2-person-cab	
<b>ENGINE</b>	Kubota 4-cylinder-4-stroke diesel		Kubota 4-cylinder-4-stroke turbo diesel	
<b>Emission standard</b>	Stage 5			
<b>Power</b>	42 kW (57 HP)		48 kW (65 HP)	
<b>Displacement</b>	2615 cm <sup>3</sup>			
<b>Torque</b>	167,5 Nm		225,0 Nm	
<b>Rated speed</b>	2700 rpm		2400 rpm	
<b>Cooling system</b>	Water cooling			
<b>Fuel tank capacity</b>	65 l			
<b>DRIVE</b>	Hydrostatic traction drive, controlled digital-electrically, stepless road speed control, suspended front and rear axle			
	Permanent four-wheel drive via four wheels of the same size		PowerDrive via four wheels of the same size	
<b>Speed</b>	0 – 40 km/h			
<b>Differential lock</b>	Mechanical at the front and rear, simultaneously switchable electrohydraulically, acts on both axles at 100 %			
<b>Brakes</b>	Hydraulically actuated drum brake on the front axle, acts on all four wheels as four-wheel brake via the hydrostatic traction drive, electrically actuated stop brake on the front axle		Hydraulically actuated four-wheel brake, electrically actuated stop brake on the front axle	
<b>PTO shafts</b>	Front: - Rear: hydraulically powered, 540 rpm, Size: 1 3/8 inch	Optional: power-switchable, independent PTO shaft, can be switched separately at the front and rear, front: mechanically powered, 1000 rpm or optionally 540 rpm Rear: hydraulically powered, 540 rpm, Size: 1 3/8 inch		
<b>HYDRAULICS</b>	Hydraulic pump 35 l/min optionally extendable with additional device variable displacement pump 80 l/min		Hydraulic pump 35 l/min optionally extendable with additional device variable displacement pump 70 l/min	
<b>Quantity of hydraulic oil</b>	37 l		37 l	
<b>Lifting force</b>	Front 1100 kg / rear 1100 kg			
<b>Three-point lift</b>	Standard three-point, arrester hook steplessly adjustable from CAT IN to CAT I			
<b>Additional control valves</b>	High expandability, adapted for the purpose			
<b>WEIGHTS</b>	Including driver at 75 kg, depending on tyres and equipment			
<b>Empty weight</b>	1928–2445 kg		SC: 1928 – 2445 kg TC: 2089 – 2603 kg	
<b>Permissible total weight</b>	3500 kg		3500 – 3800 kg	3500 – 4000 kg
<b>Permissible axle load</b>	Front 2300 kg / rear 2300 kg			
<b>Tow bar load on the trailer coupling</b>	Max. 600 kg			
<b>Towing capacity</b>	Unbraked 1500 kg / overrun braked 3500 kg			
<b>Maximum payload (40 km/h)</b>	1572 kg		SC: 1872 kg TC: 1711 kg	
<b>DIMENSIONS</b>	Depending on tyres and cab mounting			
<b>Wheelbase</b>	1820 mm		SC: 1820 mm TC: 1870 mm	
<b>Total length</b>	2928–3770 mm		SC: 2928 – 3770 mm TC: 3301 – 4190 mm	
<b>Total height</b>	1985 mm	2010–2260 mm	SC: 2010 – 2260 mm TC: 2220 – 2272 mm	SC: 2050 – 2260 mm TC: 2220 – 2272 mm
<b>Total outer width</b>	1170–1530 mm		SC: 1170 – 1530 mm TC: 1360 – 1530 mm	
<b>Turning circle radius</b>	1170–1530 mm		SC: From 1490 mm TC: From 1620 mm	
<b>Inner flatbed dimensions</b>	1250 x 1060 x 300 mm or 1330 x 1260 x 300 mm			