


| MODELS  | FARMALL 55A                                      |
|---|--|
| ENGINE  |  |
| Number of cylinders, Type                       | 4, Turbocharged                                  |
| Capacity (cm³)                                  | 2,200  |
| Rated engine power (kW/hp(CV))                  | 41 / 55  |
| Rated engine speed (rpm)                        | 2,700  |
| Fuel tank capacity (I)                          | 51   |
| TRANSMISSION                                    |  |
| Standard  | 8 Fwd / 8 Rev synchronised                       |
| Shuttle type                                    | Synchronised Mechanical Shuttle                  |
| DRIVE AND STEERING                              |  |
| Front axle standard                             | 2 wheel drive                                    |
| Front axle optional                             | 4 wheel drive with limited slip differential     |
| 4wd operation                                   | mechanical engagement                            |
| POWER TAKE OFF                                  |  |
| Туре  | mechanical engagement                            |
| Rear pto speeds (rpm)                           | 540  |
| HYDRAULIC SYSTEM                                |  |
| Pump flow - steering (I/min)                    | 20   |
| Pump flow - hitch and external services (I/min) | 44   |
| Remote valves                                   | 1 standard (2nd valve optional)                  |
| Rear linkage control                            | Mechanical Hitch Control, Top link draft sensing |
| Rear lift capacity (kg)                         | 1,500  |
| WEIGHTS AND DIMENSIONS                          |  |
| Minimum weight 2WD / 4WD (kg)                   | 1,750 / 1,970                                    |
| Overall length (mm)                             | 3,331  |
| Max height, ROPS upright / ROPS folded (mm)     | 2,435 / 1,975                                    |
| Min width (mm)                                  | 1,680  |
| Wheelbase 2WD / 4WD (mm)                        | 1,976 / 1,960                                    |
| STANDARD TYRES                                  |  |
| Front 2WD / 4WD                                 | 6.00 x 16 / 9.5R24                               |
| Rear  | 14.9R28  |







⚠ Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment.

CNH UK Ltd., Cranes Farm Road, Basildon, Essex SS14 3AD - © 2012 CASE IH - FARMALL A -COM-LF www.caseih.com - Free phone 00800 22 73 44 00 - Printed in Italy - 01/12 - TP01 - Cod. 11C0013/INB

