

# Chieftain 400 & Chieftain 600



The Powerscreen® Chieftain 400 and 600 are designed for smaller end users or contractors looking for an affordable entry level screening unit. These entry level machines share many of the class leading features of the larger models in the range including remote tipping grid, main conveyor, high performance 2 deck screen and hydraulically folding conveyors.

### Features & Benefits

- Direct feed – Chieftain 400
- Integrated high capacity variable speed belt feeder – Chieftain 600
- Radio controlled tipping grid
- Grease filled 4 bearing, 2 deck screen box
- Hydraulic screen angle adjustment
- Hydraulic screen tensioning
- Screen walkway and access ladder
- Hydraulic folding conveyors with excellent stockpiling capacity
- Engine protection shutdown system

### Options

- Wheel or track mobile
- Double deck vibrating grizzly
- Radio controlled tracking
- Electric wheel version
- Anti roll-back



Output Potential: Chieftain 400: up to 150 tph (165 US tph)\*  
 Chieftain 600: up to 200 tph (220 US tph)\*

Chieftain 400	Track	Wheel	Chieftain 600	Track	Wheel
Weight (Est)	13,020kgs (28,704lbs)	11,280kgs (24,868lbs)	Weight (Est)	15,200kgs (33,510lbs)	14,040kgs (30,952lbs)
Transport width	2.75m (9')	2.75m (9')	Transport width	2.75m (9')	2.75m (9')
Transport length	10.2m (33'6")	10.75m (35'3")	Transport length	12.45m (40'6")	12.45m (40'6")
Transport height	3.2m (10'4")	3.9m (12'10")	Transport height	3.2m (10'4")	3.5m (12'11")
Working width	11.35m (37'3")	11.35m (37'3")	Working width	11.27m (36'8")	11.27m (36'8")
Working length	11.5m (37'9")	11.8m (38'9")	Working length	13.68m (44'6")	13.68m (44'6")
Working height	4.45m (14'7")	4.65m (15'3")	Working height	4.5m (14'8")	4.76m (15'6")
Screen unit	2.44m x 1.22m (8' x 4')	2.44m x 1.22m (8' x 4')	Screen unit	2.44m x 1.22m (8' x 4')	2.44m x 1.22m (8' x 4')

