

COUGAR PTO



FOLDABLE HOPPER FOR TRANSPORT OF THE CHIPPER/SHREDDER WHEN COUPLED TO TRACTOR



PATENTED MIXED ROTOR™
Equipped with 6 hammers - without grease nipple - with inserts and 2 blades.



TRANSMISSION
Gearbox driven rotor
Safety coupling.



HYDRAULIC CONNECTIONS



VARIOSTRESS
Pre-set No Stress program adjustable for the type of material to be processed.

TECHNICAL CHARACTERISTICS

Product Code	1425331
Engine	With PTO Shaft
Engine swept volume cm ³	Torque 540 Rpm
Fuel	Min. lifting power. min. 25 hp
Cowling	ABS safety hoods
Admissible Diameter	11 cm
Output	10 m ³ /h
Rotor Diameter	560 mm
Rotor Weight	40 kg
Hammers	6
Knives	2
Large feed roller	Yes
Feed roll width	190 mm
Feed Conveyor	Non
Feed roll diameter	180 mm
Allowable Road weight axles	-
No. Of axles	-
Tyre dimensions	-
Tank capacity	-
Consumption	-
Multidirectional chimney	270°

Chimney outlet height	1 850 mm
Machine weight	450 kg
PTAC trailer approval	-
Hopper dimensions (L x W)	1 550 x 850 mm
Hopper Loading height	840 mm
L x W x H	1 900 x 1 400 x 1 600
Guaranteed acoustical power level rating	-

OPTIONS

Option CO2 Reduction	-
Insert ref.	RHEV/0010 (6)
Knife ref.	RHEMVV/0020 (2)
Spare wheel ref + Spare wheel support ref.	-
Wheel chock ref. (2)	-
Stabilizer legs ref.	-

Machine directive: 2006/42/CE. Harmonized standards used: EN 13525. **Specify your hitch type at the time of your order.**



TS Industrie GmbH
Weserstrasse 2
47506 NEUKIRCHEN-VLUYN
DEUTSCHLAND
Telefon : +49(0)2845 9292-0
Telefax : +49(0)2845 9292-28
kontakt@ts-industrie.eu

TS INDUSTRIE FRANCE
3 rue Jules Verne - L'Orée du Golf
BP 17 - 59790 RONCHIN
FRANCE
Tél : +33 (0)3 20 43 87 87
Fax : +33 (0)3 20 34 12 73
contact-industrie@saelen.fr

ERIC HUNTER Ltd
Prince Albert House 20 King Street;
Maidenhead,
Berkshire SL6 1DT - UK
Phone: +44(0)1628 778 644
Fax: +44(0)1628 778 633
contactuk@eric-hunter.com

www.ts-industrie.eu