

CultiTrail







Heavy duty trailed seedbed cultivator Working width 5 and 6 m





Standard equipment

- · Crackerboard, hydraulically operated
- 5 rows of 45x10 mm curved tines
- 4 pcs of 300/55-14.5 wheels
- Road lights

Optional equipment

- 330/300 mm diameter Crosskill roller
- 5 rows of 45x10 mm straight tines (in lieu of curved tines)
- · Levelling bar in front of the Crosskill roller
- · Rear harrow

Cultitrail is a heavy duty trailed seedbed cultivator with a high capacity. It starts with a hydraulically adjustable Crackerboard for crushing clods and leveling off followed by 5 rows of tines with a very good clearance between each row. The closest tine distance is 400 mm ensuring good flow and minimal risk of material blockages. Without use of tools the working depth is controlled by a stroke limiter on the 2 central lifting cylinders. Hence 4 radial wheels effectively carry the machine, which is concluded by a spring tine rear harrow.



A 330/300 mm Crosskill roller can be fitted at the rear of the cultivator. The soil is consolidated and the working depth is controlled very precisely. Made out of steel, the weight is limited, maintaining the superb cultivation effect of the Crosskill ring style.



Despite its wide working width CultiTrail is only 2.5 m wide in Transport position. Folding and unfolding is controlled hydraulically from the tractor seat, which makes the job very easy for the operator.



As standard CultiLift is delivered with 5 rows of 45×10 mm curved tines which give a unique cultivation effect. Alternatively 5 rows of 45×10 mm straight tines can be fitted. They are less aggressive.

Technical specifications:

Working width	5.0 m	6.0 m
Hp requirements from	100 Hp	125 Hp
No of tines	63 pcs	77 pcs
No of Crackerboard tines	18 pcs	22 pcs
No of rear harrow tines	42 pcs	50 pcs
Weight	2,300 kg	2,500 kg
Transport width	2.5 m	2.5 m
Transport height	2.9 m	3.4 m

DAL-BO – SIMPLE AND ROBUST

