



**EL8-T
EL10-T**

STANDART FEATURES

- Proportional control
- Emergency stop button
- Cylinder holding valve
- Non-marking tyre
- Automatic pothole protection
- Onboard diagnostic system (Platform and Ground)
- Emergency lowering system
- Platform extention
- Horn
- Lifting with forklift and crane
- Charger protection
- All motion alarm
- Maintenance bar
- Hour meter
- Flashing beacon
- Integrated tilt sensor with alarm
- Pressure sensor

ADVANTAGES

- Rigid structured and unique design
- Easy parts replacement
- Safe driving at full height
- High maneuverability
- CAN communication protocol
- CE-EN280 certificate
- 220 V power outlet and cable on platform



DIMENSIONS

	EL8-T	EL10-T
Working Height	8 m	10 m
A Platform Height	6 m	8 m
B Stoved Height (Platform)	1.01 m	1.20 m
C Stoved Height (Guardrails)	2.11 m	2.31 m
D Transport Height	1.62 m	1.82 m
E Ground Clearance-With Pothole Guards Deployed	0,02 m	0,02 m
F Ground Clearance-Center	0,12 m	0,12 m
G Width	0,80 m	0,80 m
H Wheelbase	1.86 m	1.86 m
I Length	2.31 m	2.31 m
J Length With Access Steps	2.47 m	2.47 m
K Platform Width	0,83 m	0,83 m
L Platform Length	2.30 m	2.30 m
M Platform Extension	0,86 m	0,86 m

TECHNICAL SPECIFICATIONS

Distributed Capacity of Main Platform	350 kg	240 kg
Distributed Capacity of Extension	150 kg	150 kg
Gradeability	%25	%25
Lift-Lower Time	35 / 35 sec	45 / 45 sec
Non Marking Tyres	Solid 15 x 5	Solid 15 x 5
Hydraulic Tank	25 L	25 L
Electric Motor and Hydraulic Pump	24 V / 4,5 kW / 3,8 cc	24 V / 4,5 kW / 3,8 cc
Batteries	4 x 6 V 232 Ah	4 x 6 V 232 Ah
Battery Charger	24 V / 20 A	24 V / 20 A
Weight	1800 kg	1975 kg

