

tracboy



Elektro-Schlepper aus eigener Herstellung.

Übersicht technische Daten

Characteristic

				Balkancar	Balkancar	Balkancar	Balkancar
1	Hersteller			ES 125	ES 250	ES 350	ES 400
2	Typ			1	2	2	2
3	Sitze	Anzahl		1.250	2.500	3.500	4.000
4	Nennzugkraft		N	6.000	12.000	16.000	20.000
5	Schleppvermögen		kg	Seat-steering	Seat-steering	Seat-steering	Seat-steering
6	Lenkungsart	walking, standing, (driver-)seat-steering		L / L; SE / SE	L / L; SE / SE	L / L; SE / SE	L / L; SE / SE
7	Bereifung	L = pneumatic, SE = superelastic front / rear		1 / 2x	2 / 2x	2 / 2x	2 / 2x
8	Räder (x = angetr.)	Menge vorn/hinten					

Dimensions

9		L	Länge	mm	1650	2450	2750	3060
10	Maße ü. alles	B	Breite	mm	965	1220	1350	1360
11		h3	Kabinenhöhe	mm	-	2240	2240	1850
12	Wenderadius	Wa		mm	1360	2200	2450	2780
13	Kupplungshöhe	hA		mm	280-420	280-440	280-440	280-440

Performance

14	Geschwindigkeit	mit / ohne Last	km/h	7,5 / 13	8 / 14	9 / 15	8 / 13
15	Steigfähigkeit	mit / ohne Last	%	4 / 12	4 / 12	6 / 20	6 / 20

Chassis

16	Eigengewicht	einschl. Batterie	kg	760	1725	2240	2500
17	Radstand	y	mm	890	1200	1075	1360
18	Bodenfreiheit	an tiefster Stelle mit Last	mm	85	125	90	90
19	Betriebsbremse	mech. / hydr. / electr.		hydr.	electr. / hydr.	electr. / hydr.	electr. / hydr.
20		Anzahl gebremster Achsen	Stk.	1	2	2	2
21	Feststellbremse	Fuß-, Hand-bremse		Hand	Hand	Hand	Hand
22	Federung			rigid	rigid	rigid	rigid

Drive

23		DIN 43 535/36		PzS	PzS	PzS	PzS
24	Batterie	Spannung / Kapazität	V / Ah	40 / 320	2x40 / 280	2x40 / 330	2x40 / 400
25		Typ		DC	DC	DC	AC
26	Elektromotor	Drive motor, Power (KB 60 min)	kW	3,0	6,3	9	16
27	Schaltung	with electric drive	Type	Impulse ctrl.	Impulse ctrl.	Impulse ctrl.	Impulse ctrl.
28	Anhängerkupplung		Type	Socket Pins	Socket Pins	Socket Pins	Socket Pins

