




ENDRESS

Power Generators

ESE 1204 DHS-GT ES ISO DI

Order No. **122005**



Main features

| | |
|------------------------------|-----------|
| Alternator type | synchron |
| Max. Output 3~ [kVA/kW] | 15,8/12,6 |
| Max. Output 1~ [kVA/kW] | 10.4/9.4 |
| Continuous Power 3~ [kVA/kW] | 11.0/8.8 |
| Continuous Power 1~ [kVA/kW] | 6.5/5.8 |
| Nominal voltage [V] | 400/230 |
| Nominal Current [A] | 15,9 |
| Power factor cos (phi) | 0,9 |
| Frequency [Hz] | 50 |
| Protection Class [IP] | 23 |

Engine

| | |
|--|--|
| Engine Type | HATZ 2G 40 / 20 HP |
| Design | 2-cylinder 4-stroke |
| Displacement [ccm] | 997 |
| Output 3000 rpm | 15,4 |
| CO2 emissions [g / kWh] | 806,73 |
| CO2 test procedure | NRSC-D2 |
| Fuel | Diesel |
| Fuel tank capacity [l] | 17 |
| Fuel consumption @ 75% PRP [L/h] | 2,3 |
| Running time @ 75% PRP | 7,4 |
| Starting system | E-Start incl. battery |
| Sound power level LWA [db(A)] | 97 |
| Sound pressure level LPA (7 m) [db(A)] | 72 |
| Weight in kg ca. | 275 |
| Dimensions L x W x H [mm] | 1270 x 610 x 920 |
| Shockproof sockets | 1 x CEE 230 V/16 A 1 x CEE 230 V/32 A 1 x CEE 400 V/16 A |

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2020-2-19

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



ESE 1204 DHS-GT ES ISO DI

Order No. 122005



Power Generators

Equipment features

Noise insulating housing for low operating noises

Large fuel tank for long running times

Alternator overload protection

Compound regulated high performance generator

Insulation monitoring

Voltmeter

Crane loading lug

Starter battery 12 V

Wheelset as standard

Possible applications

400V

230V

Electric tools up to

8700W

5700W

Gardening or construction equipment up to

5800W

3800W

Compressors or pumps up to

4400W

2900W

Inverter welding equipment up to a dia. of 4.50 mm

Special equipment - not retrofittable

Order No.

Cable remote control (20 m)

162 023

выразить любую гарантию работы конкретного двигателя.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2020-2-19

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

