


## EXCAVATORS



	PC02	PC04
Bucket capacity	0.10 m <sup>3</sup> (0.13 cu.yd)	0.08 ~ 0.21 m <sup>3</sup> (0.10 ~ 0.27 cu.yd)
Flywheel horsepower	20 HP/2200 RPM	30 HP/2500 RPM
Operating weight	2550 kg (5,620 lb)	4200 kg (9,260 lb)
Travel speed	1.7 km/h (1.1 MPH)	2 km/h (1.2 MPH)
Swing speed	12.5 RPM	10.5 RPM
Max. digging depth	2500 mm (98.4")	3200 mm (126.0")
Max. digging height	3440 mm (135.4")	4765 mm (187.6")
Max. dumping height	2300 mm ( 90.6")	3100 mm (122.0")
<b>C</b> Overall length (shipping)	4270 mm (168.1")	5235 mm (206.1")
<b>B</b> Overall height (to top of operator's cab)	2285 mm ( 70.0")	2360 mm ( 92.9")
Overall width	1470 mm ( 57.9")	1750 mm ( 68.9")
Ground pressure	0.25 kg/cm <sup>2</sup> (3.56 PSI)	0.28 kg/cm <sup>2</sup> (3.98 PSI)
No. of track rollers	4	5
<b>A</b> Length of track on ground	1535 mm (60.4")	1730 mm (68.1")
Track shoe width	300 mm (11.8")	400 mm (15.7")

## WHEEL BACKHOE



	WB04
Bucket capacity	0.06 m <sup>3</sup> (0.065 cu.yd)
Flywheel horsepower	10 HP/3000 RPM
Operating weight	1205 kg (2,660 lb)
Transmission/travel speeds	Hydrostatic/0 ~ 10 km/h (6.2 MPH), forward and reverse
Max. drawbar pull	500 kg (1,100 lb)
Min. turning radius	2.8 m (9.2 ft)
Digging force	1500 kg (3,310 lb)
Max. digging reach: Upward Downward	3215 mm (126.6") 2150 mm ( 84.6")
Max. loading height	1950 mm ( 76.8")
Swing angle: Right Left	180° 90°
<b>A</b> Overall length (in traveling)	3565 mm (140.4")
Overall width (in traveling)	1290 mm ( 50.8")
<b>B</b> Overall height (in traveling)	1965 mm ( 77.4")
<b>C</b> Wheelbase	1250 mm ( 49.2")
Blade width	1290 mm ( 50.8")
Blade height	435 mm ( 17.1")



WB04