

FARM 2000



The FARM 2000 tire is suitable on tractors for soil tillage and transport applications. It is the ideal tire for heavy-duty use and in all operating conditions where good traction is required.

MACHINERY

 AGRICULTURE

IMPLEMENT MACHINERY - TRACTOR

APPLICATIONS

 AGRICULTURE

HAULAGE - SOIL TILLAGE

PLUS



TRACTION



DURABILITY



HEAVY DUTY SERVICE

TECHNICAL DATA U/M: INTERNATIONAL STANDARD (MM)

Size	Version	LI/SS	PR	RIM REC	SW	OD	SLR	RC	Type	TKPH	TRA Code
260/70 - 15.3				9.00	265	775	349	2294	TL		
300/80 - 15.3				9.00	300	890	388	2608	TL		
250/80 - 16				W 8	240	820	369	2429	TT		
250/80 - 16				W 8	240	820	369	2429	TL		
8 - 18			4	W 6	195	840	390	2470	TT	0	
8 - 18			6	W 6	195	840	390	2470	TT	0	
250/80 - 18				W 8	240	870	394	2679	TT		
250/80 - 18				W 8	240	870	394	2679	TL		
8.3 - 20			4	W 7	210	895	431	2714	TT		
8.3 - 20			6	W 7	210	895	431	2714	TT		
8.3 - 24			6	W 7	211	995	473	3032	TT		
8.3 - 24			8	W 7	211	995	473	3032	TT	0	
12.4 - 28		123 A6	8	W 11	320	1288	603	3969	TT		R-1
12.4 - 28		127 A6	10	W 11	320	1288	603	3969	TT		R-1
12.4 - 28		131 A6	12	W 11	320	1288	603	3969	TT	0	R-1
13.6 - 28		121 A6	6	W 12	345	1335	622	4080	TT		R-1
13.6 - 28		125 A6	8	W 12	345	1335	622	4080	TT		R-1
13.6 - 28		127 A6	10	W 12	345	1335	622	4080	TT		R-1
13.6 - 28		128 A6	12	W 12	345	1335	622	4080	TT		R-1
14.9 - 28		130 A6	8	W 13	385	1375	636	4194	TT		R-1
14.9 - 28		134 A6	10	W 13	385	1375	636	4194	TT		R-1
14.9 - 28		137 A6	12	W 13	385	1375	636	4194	TT		R-1
14.9 - 28		139 A6	14	W 13	385	1375	636	4194	TT		R-1
16.9 - 28	HD	135 A6	8	W 15 L	429	1420	657	4351	TT		R-1
16.9 - 28		143 A6	12	W 15 L	429	1420	657	4351	TT		R-1
18.4 - 30		151 A6	14	W 16 L	470	1560	716	4776	TT		R-1