

# Metrac G3 X

**NEW!**



## Technical data – basic equipment:

**Engine:** 4 cylinder 4 stroke diesel engine, Kubota V 2003 M EU-32, stage 3A, 32.1 kW (44 hp) at 2800 rpm, displacement 1999 cm<sup>3</sup>, water-cooled.

**Gearbox:** Shuttle gearbox with 8 forward and 8 reverse gears, Speed: 2.3 – 23.0 kph (29" tyres)

**Clutch:** Single-disk dry clutch for travel drive and rear PTO (via clutch pedal), multi-disk clutch for front PTO drive (hand lever operated).

**Axes:** Driving/steering with final drives front and rear, front axle oscillating.

**Axle drive:** Four wheel drive, front-wheel drive switchable.

**Differential locks:** Self-locking differential front, manual differential lock rear.

**Steering:** Hydrostatic steering with Load Sensing; electro-hydraulic steering switch during driving, pre-selectable with options for 4 wheel, front, rear, and continuously adjustable crab steering; automatic synchronisation of wheel position.

**Service brake:** Hydr. dual circuit 4 wheel power brake.

**Parking brake:** Mechanical parking brake and steering brake mechanism acting on front wheels.

**Engine hydraulics:** Hydraulic pump 26.6 l/min, 180 bar, oil tank 8 l, standard equipment var. B1: 1 control valve each for front and rear linkage, 1 control valve d.a.f. with parallel lines front and rear; option: Var. C1: 1 additional control valve d.a.f. with parallel lines front and rear (max. 4 trailer couplings front and 4 rear)

**Front linkage:** Front 3 point linkage with hydraulic weight compensation, quick release system via seating locators, top link mount, lifting force max. 900 kg.

**PTO:** Power shift PTO front 540 rpm, counter-clockwise, gearbox PTO rear 540 rpm, clockwise (direction of rotation: looking at PTO shaft end).

**Cab:** Driver rollover protection frame with roof and tinted windscreen, side window right and rear window, comfort seat, wiper with windscreen washer, cable lead-through for attachments. Option: Closed cab with door, sliding window and heating.

**Gauges:** Tachometer with integrated operating hours meter, fuel gauge, remote thermometer, indicator for straight wheel alignment, various indicator lights with symbols.

**Electric system:** Battery 12 V, 60 Ah, alternator 45 A, full road lighting, complete, Option: Auxiliary lights front on roof, 1 working light rear, rotating warning light.

**Fuel tank:** PE tank, capacity 35 l.

**Seat designs:** Comfort seat with leatherette cover, pelvic support, longitudinally and height adjustable, tilt-adjustable backrest;

Option: High backrest, protective cloth cover, arm rest, seat belt.