

Technical data

HC 200i



Soil Compactors Series HC
Soil compactor with smooth drum

H256

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 200i (H256)

Weights

Operating weight with cab	kg	19240
Operating weight with ROPS	kg	18905
Basic weight no cab, without ROPS	kg	18035
Operating weight, max.	kg	21740
Axle load, front/rear	kg	13155/6085
Axle load max., front/rear	kg	14930/6810
Static linear load, front	kg/cm	61,67
French classific., data/class		87,3/VM5
Load per tyre, rear	kg	3042,5

Machine dimensions

Total length	mm	6659
Total height with cab	mm	3064
Total height with ROPS	mm	3064
Height loading, min.	mm	3064
Wheel base	mm	3312
Total width with cab	mm	2474
Max. working width	mm	2140
Ground clearance, centre	mm	471
Kerb clearance, left/right	mm	517/517
Turning radius, inside	mm	4278
Angle of driving slope, front/rear	°	36,6/25,7

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1600
Drum thickness, front	mm	45
Drum type, front		smooth

Wheel dimensions

Size of tyres, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2140
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Version		TCD 6.1 L6
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		160,0/217,7/2000
Power rating SAE J1349, kW/HP/rpm		160,0/214,7/2000
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Drive

Speed, infinitely variable	km/h	0 - 11,9
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	51/57

Vibration

Vibration frequency, front, I/II	Hz	27/30
Amplitude, front, I/II	mm	2,20/1,25
Centrifugal force, front, I/II	kN	350/250

Steering

Oscillation angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L	336
AdBlue/DEF tank, content	L	32

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power LW(A), measured	db(A)	104

EQUIPMENT

12 V sockets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Vibration-isolated operator's platform | Automatic vibration system | Traction Control, manual | Plastic scraper, for smooth drum

OPTIONAL EQUIPMENT

Traction Control, automatic | Plastic scraper, for smooth drum (2-fold, V-shaped) | ROPS cabin with heating and air conditioning, FOPS-approved (level I) | Safety belt monitoring device | Armrest comfort setting, left | Auxiliary heater | Tachograph | Fire-extinguisher | Bluetooth interface for Smart Doc | Dozer blade | Padfoot shells | Frequency regulation | Automatic engine-off function | Camera system | Back-up alarm (reversing) | Working lights | Rotating beacon | Bonnet with electrical easy access engine cover release | Coming home lighting | Battery isolating switch | Homologation | Additional mirror | Tool kit