



Technical data

# HC 268



## Soil Compactors Series HC

Soil compactor with smooth drum

H291

### HIGHLIGHTS

- > High compaction performance
- > Ergonomic driver platform
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for outstanding traction and off-road mobility
- > Excellent view of the machine and the construction site
- > Electronic machine management Hammtronic
- > Easy maintenance and servicing

## TECHNICAL DATA HC 268 (H291)

## Weights

Operating weight with cab	kg	24990
Operating weight, max.	kg	25680
Axle load, front/rear	kg	13875/11115
Axle load max., front/rear	kg	14130/11550
Static linear load, front	kg/cm	64,8
French classific., data/class		92,1/VM5
Load per tyre, rear	kg	5557,5

## Machine dimensions

Total length	mm	6847
Total height	mm	3301
Height loading, min.	mm	2803
Wheel base	mm	3433
Total width	mm	2350
Max. working width	mm	2140
Ground clearance, centre	mm	441
Kerb clearance, left/right	mm	505/505
Turning radius, inside	mm	5159
Angle of driving slope, front/rear	°	35/29

## Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1600
Drum thickness, front	mm	45
Drum type, front		smooth

## Wheel dimensions

Size of tyres, rear		EM 23.5-R25 PR
Width over tyres, rear	mm	2235

## Diesel engine

Manufacturer		CUMMINS
Version		QSB5.9-C210-30
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		154/209/2200
Power rating SAE J1349, kW/HP/rpm		154/206/2200
Emission standard		MEE III
Exhaust gas after-treatment		-

## Drive

Climbing ability, vibration on/off	%	22/24
------------------------------------	---	-------

## Vibration

Vibration frequency, front, I/II	Hz	27/30
Amplitude, front, I/II	mm	2,02/1,20
Centrifugal force, front, I/II	kN	331/242

## Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

## Tank capacity/Fill capacity

Fuel tank, capacity	L	321
---------------------	---	-----

## Sound level

Acoustic power LW(A), measured	db(A)	
--------------------------------	-------	--

## EQUIPMENT

Dashboard with displays, indicator lights and switches | Operator's platform with access on one side | Vibration-isolated operator's platform | Seat longitudinal adjustment | 1 drive lever | ECO mode | Tilttable bonnet | Hydrostatic steering | 3-point articulation | Adjustable scraper | Plastic protective roof, reinforced with fibre glass and foldable

## OPTIONAL EQUIPMENT

Cab with heating and air-conditioning system | | HCQ Navigator | HAMM Compaction Meter (HCM) | Back-up alarm (reversing) | Working lights | Rotating beacon | Tool kit