

M70PSC - UTILITY AG TRACTOR









MODEL	M70PSC
Engine – TCD 2.9L4 T4F	4 - Cylinder Common Rail, Water Cooled, TURBOCHARGED Diesel
Engine Horse Power per ISO 143961	75 Max (55.4kW) • 73.2 Rated (54.5kW) • 67 Net (50kW)
Power Take Off (PTO) HP	62
Transmission Design	24F/24R, 4 - Range, 4 - Speed
Transmission Features	(5) Factory Creeper Speeds
Transmission Drive	Synchronized Power Shuttle Reverser
Power Take-Off (PTO)	540/540E/1000 Rear, Hydraulic Independent with Manual, Off and Auto Control
PTO Engagement	Electro-Hydraulic, 2-Position Knob
CAT II, 3-Point Hitch	HD Telescopic Stabilizers and Extendable Lower Link Ball Ends, Sliding/Swinging Drawbar
3-Point Hitch Control	Mechanical Controls: Position • Draft • Mix • Speed Sensitivity • Safety Stop
3-Point Hitch Lift Capacity	4,270 Lbs. (1937 kg)
Hydraulic Total Flow	16.1 GPM (61.1 L)
Rear Valves	2 - Standard, 3 - Optional
Mid Valves	2 - Standard with 4 - Couplers & Factory Joystick with 3rd Function Control
3rd Function	Optional 3rd Function Hydraulic Kit
Total Hydraulic Flow	16.1 GPM (61.1 L)
Power Steering Flow	5.8 GPM (22 L) with Tilt
QA Front End Loader	MSL Quick Attach with 78" Bucket, Skid Steer Style Carrier
Loader Lift Height	124.8 in (3169 mm)
Loader Max Lift Capacity	3,122 Lbs. (1416 kg)
STD R1 Front Tire Size	9.5 – 20 (Opt 280/85R20)
STD R1 Rear Tire Size	14.9 – 28 (Opt 380/85R30)
Operator Platform	Premium Climate Control CAB • AC • Heater • Defrost • Fresh Air Roof Hatch • Opening Corners, Rear Window
Max Height inch (STD R1)	100.2 (2545 mm)
Complete Package Weight (Std R1)	7,660 Lbs. (3,474 kg)





3-Point Hitch Position • Draft • Mix 2 - Rear Remotes



FOLLOW US









www.facebook.com/ZetorNorthAmerica www.twitter.com/ZetorNA

www.youtube.com/TraktoryZetor

ZETOR NORTH AMERICA 5784 Mining Terrace Jacksonville, FL, USA 32257 PH: 904-647-7169

Fax: 904-647-9346 www.ZetorNA.com Service@ZetorNA.com