

GREEN/SERIES



PATENTED MIXED ROTOR



ECO MIXED CHIPS



BIO DEGRADABLE LUBRICANT



270° ADJUSTABLE CHIMNEY



HYDRAULIC CLUTCH



ELECTRIC CONTROL



VARIOSTRESS


SIMPLE TO LOAD AND SAFE FOR OUTSTANDING EASE OF USE

1




1- WIDE AND EASILY ACCESSIBLE FEED HOPPER with transparent curtain

2



2- PATENTED MIXED ROTOR with 10 hammers with replaceable heads and 2 cutting blades

3



3- CLUTCH: TURBO SAFETY CLUTCH  
Thermal safety 145°  
Thermal safety 180°

4



4- HYDRAULIC OIL FLOW DIVIDER

TECHNICAL DATA

Product code	GSPREMIUM22P	No of axles	1/1300 kg
Engine	B&S VANGUARD 23 HP/ 16,18 kW	Allowable road weight axles	
Engine swept volume cm3	627 2-Cyl.	Tyre dimensions	155/70R13
Fuel	Petrol	Tank capacity	30 L
Clutch	Hydraulic clutch	Consumption	4,5 L/h
Cowling	ABS Safety hoods	Multidirectional chimney	270°
Admissible diameter	13 cm	Chimney outlet height	2060 mm
Output	13 m3/h	Machine weight	745 kg
Rotor diameter	560 mm	MMTA trailer approval	750 kg
Rotor weight	83 kg	Hopper dimensions (LxW)	1400 x 1390 mm
Hammers	10	Hopper loading height	670 mm
Knives	2	L x W x H	3770 x 1600 x 2140 mm
Feed roll width	250 mm		
Feed conveyer	No		
Feed roll diameter	340 mm		