



# RHINO EQUIPMENT



Tandem Compactors	Rhino RCT40H		CAT CB 34B XW		Ammann ARX36		Bomag BW 135AD		Dynapac CC1300		Hamm HD12VV		Intensus TD40		JCB VMT 380-140		Powerpac CT348H-iii		Sakai SW 502S-1		Volvo DD38HF	
<b>Engine</b>																						
Manufacturer	Rhino		CAT		Yanmar		Kubota		Kubota		Kubota		Deutz		Kohler		Kubota		Kubota		Kubota	
Model	ZN390Q		C2.2		4TNV88		V2203		V2203M		V2203-M-E3B		F3L 1011 F		KDW 2204		V 2203 KA		V2203 EDM		V 2203 M	
Emission Rating	Tier 2		Tier 4		Interim Tier 4		Interim Tier 4		N/P		Interim Tier 4		N/P		Interim Tier 4		N/P		Interim Tier 4		Interim Tier 4	
Displacement L (in3)	1.8	(110)	2.2	(134)	2.2	(134)	N/P	N/P	N/P	N/P	N/P	N/P	2.1	(125)	2.2	(134)	N/P	N/P	2.2	(134)	N/P	N/P
Engine Output kW (hp)	22	(30)	36.4	(49)	30	(40)	33	(44)	34	(46)	35	(46)	30	(40)	34	(46)	30	(40)	29	(39)	31	(42)
<b>Transmission</b>																						
Transmission Type	Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		N/P		Hydrostatic		Hydrostatic	
<b>Dimensions</b>																						
Overall Length mm (ft)	3,180	(10)	2,859	(9)	2,800	(9)	2,840	(9)	2,725	(9)	2,860	(9)	N/P	N/P	2,820	(9)	2,650	(9)	3,100	(10)	2,556	(8)
Overall Height mm (ft)	2,650	(9)	2,660	(9)	2,826	(9)	2,700	(9)	2,750	(9)	2,590	(8)	N/P	N/P	2,550	(8)	2,260	(7)	2,565	(8)	2,529	(8)
Overall Width mm (ft)	1,420	(5)	1,400	(5)	1,423	(5)	1,390	(5)	1,450	(5)	1,426	(5)	N/P	N/P	1,490	(5)	1,380	(5)	1,390	(5)	1,485	(5)
Wheelbase mm (ft)	2,200	(7)	2,050	(7)	1,950	(6)	1,900	(6)	1,925	(6)	1,950	(6)	N/P	N/P	2,020	(7)	1,948	(6)	2,300	(8)	1,725	(6)
Ground Clearance mm (in)	300	(12)	284	(11)	325	(13)	340	(13)	260	(10)	N/P	N/P	N/P	N/P	300	(12)	N/P	N/P	280	(11)	N/P	N/P
Steering Angle	35 degrees		N/P		32 degrees		32 degrees		30 degrees		33 degrees		N/P		36 degrees		30 degrees		35 degrees		30 degrees	
Inside Turning Radius mm (ft)	6,000	(20)	N/P	N/P	2,581	(8)	2,665	(9)	2,940	(10)	2,690	(9)	3,100	(10)	2,440	(8)	3,400	(11)	N/P	N/P	N/P	N/P
Outside Turning Radius mm (ft)	3,800	(12)	N/P	N/P	N/P	N/P	N/P	N/P	4,240	(14)	N/P	N/P	4,400	(14)	N/P	N/P	N/P	N/P	4,300	(14)	3,907	(13)
<b>Capacities</b>																						
Fuel Tank L (gal)	80	(21)	N/P	N/P	59	(16)	55	(15)	50	(13)	N/P	N/P	100	(26)	100	(26)	70	(18)	50	(13)	68	(18)
<b>Performance</b>																						
Liener Drum Load - Front kg/cm (lb/in)	15.0	(84.0)	13.6	(76.2)	14.4	(80.6)	15.0	(84.0)	14.5	(81.2)	15.5	(86.8)	8.7	(48.7)	13.8	(77.3)	12.1	(67.8)	N/P	N/P	12.9	(72.2)
Liener Drum Load - Rear kg/cm (lb/in)	18.4	(103.0)	13.6	(76.2)	14.4	(80.6)	15.0	(84.0)	15.4	(86.2)	15.1	(84.6)	8.7	(48.7)	13.8	(77.3)	11.4	(63.8)	N/P	N/P	14.8	N/P
Travel Speed kph (mph)	8.0	(5.0)	13.0	(8.1)	10.0	(6.2)	5.0	(3.1)	10.0	(6.2)	11.0	(6.8)	6.2	(3.9)	9.0	(5.6)	10.0	(6.2)	7.5	(4.7)	10.0	(6.2)
Vibration Frequency Hz (vpm)	50	(3,000)	55	(3,300)	57	(3,420)	52	(3,120)	52	(3,120)	67	(4,020)	N/P	N/P	66	(3,960)	N/P	N/P	55	(3,300)	70	(4,200)
Drum Vibration	Both		Both		Both		Front/Both		Both		Both		Both		Both		Both		N/P		Front / Both	
<b>Weights</b>																						
Operating Weight kg (lbs)	4,000	(8,818)	3,803	(8,384)	3,740	(8,245)	3,900	(8,598)	3,900	(8,598)	3,410	(7,518)	4,000	(8,818)	3,850	(8,488)	4,000	(8,818)	4,160	(9,171)	3,809	(8,397)

N/P=Not Published



[www.rhinoeq.com](http://www.rhinoeq.com)