



RHINO EQUIPMENT



Tandem Compactors	Rhino RCT60H		CAT CD44B		Ammann AV 70X		Bomag BW 151 AD		Case DV207		Dynapac CC2200		Hamm HD70		Sakai SW 652-1		Volvo DD70	
Engine	Rhino		CAT		Cummins		Kubota		Cummins		Deutz		Deutz		Kubota		Kubota	
Manufacturer	Rhino		CAT		Cummins		Kubota		Cummins		Deutz		Deutz		Kubota		Kubota	
Model	ZN390Q		C3.4B ACERT		BTAA 3.3		V3307 CR-T		BTAA 3.3		TCD 3.6 L4		TD 2011 L04 W		V3307 DI-T		V3600 T-E3B	
Emission Rating	Tier 2		Interim Tier 4		Tier 2		Interim Tier 4		Tier 3		Interim Tier 4		Interim Tier 4		N/P		Tier 3	
Displacement L (in3)	2.4	(146)	3.4	(207)	3.3	(201)	N/P	N/P	3.3	(201)	3.6	(220)	N/P	N/P	N/P	N/P	N/P	N/P
Engine Output kW (hp)	34	(46)	75	(101)	60	(80)	55	(74)	60	(80)	75	(101)	63	(84)	55	(74)	63	(84)
Transmission	Hydrostatic		Hydrostatic		Hydrostatic		N/P		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic	
Transmission Type	Hydrostatic		Hydrostatic		Hydrostatic		N/P		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic		Hydrostatic	
Dimensions	3,490 (11)		4,284 (14)		4,410 (14)		4,400 (14)		4,410 (14)		4,490 (15)		4,340 (14)		4,300 (14)		4,470 (15)	
Overall Length mm (ft)	3,490 (11)		4,284 (14)		4,410 (14)		4,400 (14)		4,410 (14)		4,490 (15)		4,340 (14)		4,300 (14)		4,470 (15)	
Overall Height mm (ft)	2,580 (8)		2,940 (10)		2,950 (10)		3,000 (10)		2,950 (10)		2,990 (10)		2,940 (10)		2,840 (9)		2,832 (9)	
Overall Width mm (ft)	1,550 (5)		1,500 (5)		1,540 (5)		1,844 (6)		1,540 (5)		1,620 (5)		1,610 (5)		1,615 (5)		1,626 (5)	
Wheelbase mm (ft)	2,500 (8)		3,120 (10)		3,260 (11)		3,300 (11)		3,260 (11)		3,340 (11)		3,200 (10)		3,100 (10)		2,972 (10)	
Ground Clearance mm (in)	280 (11)		273 (11)		240 (9)		250 (10)		240 (9)		270 (11)		340 (13)		N/P		N/P	
Steering Angle	35 degrees		25 degrees		34 degrees		N/P		34 degrees		32 degrees		36 degrees		39 degrees		40 degrees	
Inside Turning Radius mm (ft)	6,000 (20)		2,900 (10)		5,325 (17)		4,390 (14)		4,600 (15)		N/P		4,174 (14)		3,632 (12)		3,582 (12)	
Outside Turning Radius mm (ft)	3,800 (12)		N/P		N/P		N/P		N/P		5,190 (17)		N/P		5,100 (17)		N/P	
Capacities	120 (32)		135 (36)		110 (29)		125 (33)		110 (29)		130 (34)		140 (37)		120 (32)		140 (37)	
Fuel Tank L (gal)	120 (32)		135 (36)		110 (29)		125 (33)		110 (29)		130 (34)		140 (37)		120 (32)		140 (37)	
Performance	20.8 (116.5)		27.9 (156.2)		25.9 (145.0)		23.2 (129.9)		25.9 (145.0)		25.7 (143.9)		24.5 (137.2)		N/P		22.8 (127.7)	
Linear Drum Load - Front kg/cm (lb/in)	20.8 (116.5)		27.9 (156.2)		25.9 (145.0)		23.2 (129.9)		25.9 (145.0)		25.7 (143.9)		24.5 (137.2)		N/P		22.8 (127.7)	
Linear Drum Load - Rear kg/cm (lb/in)	23.3 (130.5)		27.9 (156.2)		24.9 (139.4)		22.0 (123.2)		24.9 (139.4)		25.7 (143.9)		23.9 (133.8)		N/P		23.8 (133.3)	
Travel Speed kph (mph)	9.0 (5.6)		7.0 (4.3)		10.0 (6.2)		12.0 (7.5)		11.4 (7.1)		12.0 (7.5)		6.3 (3.9)		13.0 (8.1)		11.3 (7.0)	
Vibration Frequency Hz (vpm)	50 (3,000)		53 (3,180)		52 (3,120)		70 (4,200)		52 (3,120)		67 (4,020)		58 (3,480)		67 (4,020)		55 (3,300)	
Drum Vibration	Both		Both		Both		Both / Front / Rear		Both		Both		Both		N/P		N/P	
Weights	6,000 (13,228)		7,400 (16,314)		7,360 (16,226)		7,600 (16,755)		7,360 (16,226)		7,700 (16,976)		7,265 (16,017)		7,460 (16,446)		6,747 (14,875)	
Operating Weight kg (lbs)	6,000 (13,228)		7,400 (16,314)		7,360 (16,226)		7,600 (16,755)		7,360 (16,226)		7,700 (16,976)		7,265 (16,017)		7,460 (16,446)		6,747 (14,875)	

N/P=Not Published



www.rhinoeq.com