

Technical sheet :



# **STACKY 10 S16 LE**

---



Technical characteristics			Metric
1.1	Manufacturer		Manitou
1.2	Model Name		Stacky 10 S16 LE
1.3	Power source		Battery
1.4	Operator type		Pedestrian
1.5	Max. capacity	Q	1000 kg
1.6	Load centre of gravity	c	500 mm
1.8	Load distance, centre of drive axle to fork	x	646 mm
1.9	Wheelbase	y	1190 mm
Weight			
2.1	Overall weight without tools		626 kg
Wheels			
3.1	Tyres type		Polyurethane
3.5.2	Number of drive wheels - Size of drive wheels		1 x 200x80
3.3	Number of load wheels - Size of load wheels		1 x 78x78
3.4	Number of castor wheels		1
3.4	Number of stabilizer wheels / Size of the stabilizer wheels		2 x 125x50
3.5	Number of front wheels / rear wheels		2 / 2
3.6	Front wheel gauge	b10	517 mm
3.7	Rear wheel gauge (minimum / maximum)	b11 / b11	1000 mm x 1380 mm
Dimensions			
4.2	Height mast lowered *	h1	1990 mm
4.4	Max. lifting height	h3	1570 mm
4.5	Height mast extended *	h4	2140 mm
4.9	Height tiller up min. / max.	h14 / h14	850 mm / 1350 mm
4.15	Fork height in low position	h13	60 mm
4.19	Overall length without tools	l1	1663 mm
4.20	Length to face of forks	l2	713 mm
4.21	Overall width / width (max. staddle legs)	b1 / b1	1100 mm / 1480 mm
4.22	Forks section / width / length	s / e / l	40 mm x 80 mm / 950 mm
4.25	Fork spread	b5	720 mm
4.26	Distance between wheel arms/loading surfaces	b4	900 mm
4.24	Fork carriage width	b3	750 mm
4.32	Ground clearance at centre of wheelbase	m2	40 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2320 mm
4.35	Turning radius	Wa	1375 mm
Performances			
5.1	Travel speed (laden / unladen)		4.50 km/h / 4.50 km/h
5.2	Lifting speed (laden / unladen)		0.14 m/s / 0.25 m/s
5.3	Lowering speed (laden / unladen)		0.16 m/s / 0.14 m/s
5.7	Gradeability (laden / unladen)		3.50 % / 5 %
5.10	Service brake		Electro magnetic
5.11	Parking brake		Handle Release
Engine			
6.1	Drive motor rating S2 60 min		0.30 kW
6.2	Lift motor rating at S3 15%		2 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Semi-Traction
6.4	Battery / Batteries capacity		24 V / 85 Ah
6.5	Battery weight (+/- 5%)		50 kg
7.2	Power (kW)		0.30 kW
Miscellaneous			
8.1	Type of drive control		AC
8.4	Sound level at the driver's ear according to DIN 12 053		65 dB(A)

# Dimensional drawing




# Tool characteristics


Tool 1,000 kg	Attachment capacity	Center of gravity of load	A1	A2	B	B1	C	D	E	E1	E2	F	Weight
			kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	
EPE 1000	1000	-	7000	730	60	-	245	-	-	-	-	320	38
FA 1000	1000	-	950	1017	-	-	45	80	40	-	-	730	123
FR 1000	1000	-	1150	1182	560	-	90	-	70	-	-	700	82
FUT 1000	300	-	795	600	1057	-	245	-	240	631	-	-	92
PLF 1000	1000	-	700	727	600	-	275	-	91	-	-	630	65
POT 1000	500	-	625	652	50	-	145	-	-	-	-	320	33

# Tools


FA: Adjustable forks




PLF: Fixed platform with drawer




POT: Jib with hook




FR: Wrapover forks




EPE: Boom



FUT: Drum handler





Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes