

## Features

- Lifting Height of up to 5.80 m
- Maximum capacity of 2,900 kg
- Clear View cab provides all round vision
- Audio-visual Load Stability indicator
- Mechanical Quick-switch coupler for efficient attachment changes
- Four-wheel steering - Front wheel, Co-ordinated and crab.
- Hydrostatic Transmission
- Four wheel drive
- 45% gradeability.

## Performance

### Maximum Lift Capacity

2,900 kg

### Capacity at full height

2,200 kg

### Maximum Forward Reach

3.16 m

### Capacity at Maximum Forward Reach

1,000 kg

### Lifting Height

5.80 m

### Reach at Maximum Height

0.80 m

### Break-out force with standard bucket

34.8 kN

### Drawbar Pull (loaded)

5,000 kg

### Carriage Rotation

142°

## Standard Specifications

### Engine

Tier III 74.9kW Deutz TCD 2012

91L Fuel Tank

10.4 L Engine Oil 15W40

16 L Coolant (radiator, hoses, engine)

### Hydraulic System

Load Sensing Type 102 l/min

### Reservoir

60 L

### Transmission

Hydrostatic

### Drive

4 x 4

### Steering

4 WS/Front Steer/Crab Steer

### Brakes

Wet multi disc

## Accessories & Options

- Air-conditioning
- Work lights on Boom
- Front & Rear Cab work lights
- Rotating Beacon
- Prepared for Radio
- Hydraulic Quick-switch Coupler
- Speedometer
- 12V Outlet
- Double Acting Rear Hydraulic Outlet
- Tow Hitch

## Attachments

Pallet Forks and Carriages

Side-shift Carriage

Fork positioning Carriage

General Purpose Bucket

Digging Bucket

4-in-1 bucket

Truss Boom

Bale Handler

Bale Forks (spike)



**Dimensions**

A. Overall Height .....	2.00 m
B. Overall Width .....	2.11 m
C. Width of Cab .....	0.89 m
D. Track width .....	1.63 m
E. Wheelbase .....	2.70 m
F. Length at front wheels .....	3.89 m
G. Length at fork-holder plate .....	4.48 m
H. Ground Clearance .....	0.34 m
Gross Vehicle Weight (closed cab CE version) .....	6,100 kg (with carriage)

*JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.*

**JLG Industries Inc.**  
Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel: +31 (0)23 565 5665  
Fax: +31 (0)23 557 2493  
e-mail address: europe@jlg.com  
[www.jlgeurope.com](http://www.jlgeurope.com)

