

Platform

- 0.91 m x 1.83 m low mount platform
- Side entry with inward swing gate
- Multiple function operation
- Full proportional drive joystick control with integral thumb steer switch
- Full proportional main boom and swing joystick control
- Variable speed dial control for telescope and platform rotate
- Selectable creep speed on drive / lift and swing functions
- 160 degree powered platform rotator
- Platform console machine status light panel ¹
- Load sensing system
- AC cable to platform

Functional Equipment & Accessories

- 3 degree tilt alarm and indicator light
- Steel tracks
- Fixed-width frame (extending axles not required)
- Lifting/tie down lugs
- Hour meter
- Ground control selector switch with key lock
- Platform tool tray
- 12V DC auxiliary power

Available Options

- 0.91 m x 2.44 m low mount platform
- 13 mm air line to platform
- Detachable rubber track pads
- On-board 2500W Generator
- SkyPowerTM Package 7,500 watt on-board generator
- SkyWelder[®] Package 250 amp welder in the platform ³
- All motion alarm
- Alarm package ⁴
- Light package ⁵
- Head and tail lights
- Flashing amber beacon
- Plugs & Sockets
- Hostile environment package ⁶
- Catalytic Purifier Muffler
- Corner storage tray

Power & Transmission

- Deutz D2011L04 (47 kW) diesel engine
- Engine distress warning/shut down system ²
- Gull-wing hoods
- Swing-out engine tray
- Spark arresting type muffler
- Control ADETM - Advanced Design Electronics System
- Hydrostatic drive transmission
- Horn

- ¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.
- ² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.
- ³ Available when integrated with the SkyPowerTM package.
- ⁴ Includes all-motion alarm and flashing amber beacon.
- ⁵ Includes platform mounted work lights and head & tail lights.
- ⁶ Includes console cover, boom wipers and cylinder bellows.

600SC

Platform height	18.36 m
Horizontal outreach	15.09 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	160°
Jib – overall length	—
Jib - range of articulation	—
A. Platform size	0.91 m x 1.83 m
B. Overall width	2.49 m
C. Tailswing (working condition)	1.10 m
D. Stowed height	2.56 m
E. Overall length	8.51 m
F. Stowed length	8.51 m
G. Ground clearance	0.38 m
Machine weight ¹	10,230 kg
Maximum ground bearing pressure	0.383 kg/cm ²
Drive speed	2.6 km/h
Gradeability	55%
Turning radius	Zero
Type of tracks ²	Steel
Tracks width	0.50 m
Diesel engine -Deutz D2011L04 ³	47 kW
Diesel engine (option) CAT 3.4	47 kW
Fuel tank capacity	148 L
Hydraulic system	141 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

² Optional detachable rubber pads available

³ With EGR.

