

## Technical specifications PL 1787



(Perfectly fitting front linkages or 3-point point hitch, fork-lift, construction equipment,...)

### Standard equipment

1 blade with safety release facility  
Depth skids  
Mechanical swivel device 30°  
Steel wear bar 150 x 15 mm, screwed  
Signal flags

### Series

Overall width	2900 mm
Operating width	2500 mm
Blade height - centre	750 mm
Blade height - side	860 mm
weight	470s kg

### UNI-290

### Accessories

Hydraulic swivel device 30°	PL 1783
Wheels, diam. 200 mm, <i>when ordered with blade</i>	PL 1555
Wheels, diam. 200 mm, <i>separate delivery</i>	PL 1556
Hydraulic pivoting device	PL 1786

### Adaptor for snow blade - series Universal

Adaptor for 3-point front linkage, cat. 2	PL 1775
Adaptor for 3-point rear linkage, cat.1 and cat.2	PL 1776
Adaptor for front-end loader Eurokipp with quick-change plate ( <i>incl. pivoted compensation</i> )	PL 1777
Adaptor for front-end loader Ökonom and Universal	PL 1778
Adaptor for self-assembly to third-party front-end loaders ( <i>straight traverse, width approx. 1,20m</i> )	PL 1779
Adaptor for forklift	PL 1780
Adaptor for quick coupling triangle (Weiste-triangle)	PL 1781
Adaptor for construction machinery (JCB, etc.)	PL 1782

